



# MEDIUM PRESSURE COOLANT SYSTEM

## EcoFlow

The EcoFlow medium pressure coolant system provides great performance at a very economical price. This system utilizes our unique “Cool-Control” system. The EcoFlow only needs to be supplied with the required voltage, and coolant from your factory machine tool’s coolant pump. When your coolant pump turns on, the EcoFlow senses this and turns on, making installation unbelievably simple. This system uses a 10 micron bag filter and has a dirty filter alarm which can be interfaced into the machine tool. As with all our systems, it can be installed on virtually any machine tool on the market. This unit has a very small footprint (15”x21”x28”) to maximize workspace around the machine tool. This system is available in both a 500 PSI and a 1,000 PSI model.

### FEATURES:

- 8 GPM up to 500 PSI (34 bar)
- Compatible with every machine
- “Cool-Control”
- Easy installation
- 230v (480v available)
- 10 micron filtration
- Output pressure gauge
- Caster wheels
- Small Footprint (15” x 21” x 28”)
- 2 year warranty



# SPECIFICATIONS:

Pressure	500 PSI (34 Bar)
Flow Rate	10 GPM
Adjustable Pressure	Yes (Pressure relief valve)
Filter	10 micron bag filter
Voltage	3 phase, 230 volt (440 volt available)
Filter elements	ICS part no. ICS-10-2

